

Copthorne®



1-800-UNILOCK | UNILOCK.COM

Copthorne[®]









Bundle Type

Thickness (mm)

Dimension mm



BASALT



STEEL BLUE



BURGUNDY RED/ BURNT CLAY/OLD OAK Sold Separately/ Blended on Site

BURGUNDY RED

BURNT CLAY

OLD OAK

65mm x 200mm x 60mm

SINGLE

60MM

2,349



STANDARD 7% x 25% x 23%" 200 x 65 x 60mm

Dimension Imperial		2 5/8" x 7 7/8" x 2 3/8"
SQFT PER	Bundle	89.20
	Layer	11.15000
	Section	-
	Stone	0.15
PER BUNDLE	Layers	8.00
	Sections	-
SOLDIER LNFT PER	SqFt	1.43
	Section	1.40
		-
	Layer	15.99
	Bundle	127.95
SAILOR LNFT PER	SqFt	4.41
	Section	-
	Layer	49.21
	Bundle	393.70
UNITS PER	SqFt	6.73
	Section	-
	Bundle	600.00
LBS PER	Layer	294
	Section	-

Bundle

ADVANTAGES

REALA™

Cast from historic street pavers

ULTIMA™

Up to 4x stronger than poured-in-place concrete

DRIVE FRIENDLY

Can handle vehicular loads

Notes: SOLD IN FULL BUNDLES ONLY and is produced and sold on a required, refundable skid. Important: A urethane rubber paver mat must be used to prevent scuffing when compacting. Please refer to the Polymeric Sand Best Practices on page 96. All measurements are nominal. Contact Unilock for more information.

Internal Use Only. ART NY